

Polyamide tube in 25 meter-box (unit of sales = 1 box)



<u>ID/OD (mm)</u> 1.8 x 3	<u>Mini bend radius (mm)</u> 15	<u>Max operating pressure (at 20°C) (bar)</u> 26	<u>Colour</u> Blue
<u>Temperature</u> - 20°C to + 80°C	<u>Construction</u> Polyamide PA 12	<u>Highlight</u> Excellent shape memory Highly resistant to chemicals	

Description				
Reference	ID/OD (mm)	Mini bend radius (mm)	Max operating pressure (at 20°C) (bar)	Colour
PAMBE 180325	1.8 x 3	15	26	Blue
PAMBK 180325	1.8 x 3	15	26	Black
PAMBE 020425	2 x 4	25	30	Blue

Reference	ID/OD (mm)	Mini bend radius (mm)	Max operating pressure (at 20°C) (bar)	Colour
PAMCL 020425	2 x 4	25	30	Clear
PAMYW 020425	2 x 4	25	30	Yellow
PAMBK 020425	2 x 4	25	30	Black
PAMRD 020425	2 x 4	25	30	Red
PAMGN 020425	2 x 4	25	30	Green
PAMBE 270425	2.7 x 4	30	15	Blue
PAMCL 270425	2.7 x 4	30	15	Clear
PAMYW 270425	2.7 x 4	30	15	Yellow
PAMBK 270425	2.7 x 4	30	15	Black
PAMRD 270425	2.7 x 4	30	15	Red
PAMGN 270425	2.7 x 4	30	15	Green
PAMBE 030525	3 x 5	30	24	Blue
PAMCL 030525	3 x 5	30	24	Clear
PAMBK 030525	3 x 5	30	24	Black
PAMBE 040625	4 x 6	35	27	Blue
PAMCL 040625	4 x 6	35	27	Clear
PAMYW 040625	4 x 6	35	27	Yellow
PAMBK 040625	4 x 6	35	27	Black
PAMRD 040625	4 x 6	35	27	Red
PAMGN 040625	4 x 6	35	27	Green
PAMBE 060825	6 x 8	55	19	Blue
PAMCL 060825	6 x 8	55	19	Clear

Reference	ID/OD (mm)	Mini bend radius (mm)	Max operating pressure (at 20°C) (bar)	Colour
PAMYW 060825	6 x 8	55	19	Yellow
PAMBK 060825	6 x 8	55	19	Black
PAMRD 060825	6 x 8	55	19	Red
PAMGN 060825	6 x 8	55	19	Green
PAMBE 081025	8 x 10	90	15	Blue
PAMCL 081025	8 x 10	90	15	Clear
PAMYW 081025	8 x 10	90	15	Yellow
PAMBK 081025	8 x 10	90	15	Black
PAMRD 081025	8 x 10	90	15	Red
PAMGN 081025	8 x 10	90	15	Green
PAMBE 101225	10 x 12	92	11	Blue
PAMCL 101225	10 x 12	92	11	Clear
PAMBK 101225	10 x 12	92	14	Black
PAMBE 121425	12 x 14	120	9.5	Blue
PAMCL 121425	12 x 14	120	9.5	Clear
PAMBK 121425	12 x 14	120	9.5	Black
PAMBE 131625	13 x 16	115	13	Blue
PAMCL 131625	13 x 16	115	13	Clear
PAMBK 131625	13 x 16	115	13	Black

