

## Polyamide tube in 500 meter-reel (unit of sales = 1 reel)



<p><b>ID/OD (mm)</b></p> <p>6 x 8</p>	<p><b>Mini bend radius (mm)</b></p> <p>55</p>	<p><b>Max operating pressure (at 20°C)</b></p> <p><b>(bar)</b></p> <p>19</p>	<p><b>Colour</b></p> <p>Blue</p>
<p><b>Temperature</b></p> <p>- 20°C to + 80°C</p>	<p><b>Construction</b></p> <p>Polyamide PA 12</p>	<p><b>Highlight</b></p> <p>Excellent shape memory</p> <p>Highly resistant to chemicals</p>	

Description				
Reference	ID/OD (mm)	Mini bend radius (mm)	Max operating pressure (at 20°C) (bar)	Colour
<b>PAMBE 0608500</b>	6 x 8	55	19	Blue
<b>PAMCL 0608500</b>	6 x 8	55	19	Clear

Reference	ID/OD (mm)	Mini bend radius (mm)	Max operating pressure (at 20°C) (bar)	Colour
<b>PAMYW 0608500</b>	6 x 8	55	19	Yellow
<b>PAMBK 0608500</b>	6 x 8	55	19	Black
<b>PAMRD 0608500</b>	6 x 8	55	19	Red
<b>PAMGN 0608500</b>	6 x 8	55	19	Green

