

Polyamide tubing in 1000 meter-reel (unit of sales = 1 reel)



<u>ID/OD (mm)</u> 2.7 x 4	<u>Mini bend radius (mm)</u> 30	<u>Max operating pressure (at 20°C (bar))</u> 15	<u>Colour</u> Blue
<u>Temperature</u> - 20°C to + 80°C	<u>Construction</u> Polyamide PA 12	<u>Highlight</u> Excellent shape memory Highly resistant to chemicals	

Description				
Reference	ID/OD (mm)	Mini bend radius (mm)	Max operating pressure (at 20°C (bar))	Colour
PAMBE 27041000	2.7 x 4	30	15	Blue

Reference	ID/OD (mm)	Mini bend radius (mm)	Max operating pressure (at 20°C (bar)	Colour
PAMCL 27041000	2.7 x 4	30	15	Clear
PAMYW 27041000	2.7 x 4	30	15	Yellow
PAMBK 27041000	2.7 x 4	30	15	Black
PAMRD 27041000	2.7 x 4	30	15	Red
PAMGN 27041000	2.7 x 4	30	15	Green
PAMBE 04061000	4 x 6	35	27	Blue
PAMCL 04061000	4 x 6	35	27	Clear
PAMYW 04061000	4 x 6	35	27	Yellow
PAMBK 04061000	4 x 6	35	27	Black
PAMRD 04061000	4 x 6	35	27	Red
PAMGN 04061000	4 x 6	35	27	Green

