

## Polyamide tubing in 1000 meter-reel (unit of sales = 1 reel)



<b><u>ID/OD (mm)</u></b> 2.7 x 4	<b><u>Mini bend radius (mm)</u></b> 30	<b><u>Max operating pressure (at 20°C (bar))</u></b> 15	<b><u>Colour</u></b> Blue
<b><u>Temperature</u></b> - 20°C to + 80°C	<b><u>Construction</u></b> Polyamide PA 12	<b><u>Highlight</u></b> Excellent shape memory Highly resistant to chemicals	

Description				
Reference	ID/OD (mm)	Mini bend radius (mm)	Max operating pressure (at 20°C (bar))	Colour
<b>PAMBE 27041000</b>	2.7 x 4	30	15	Blue

Reference	ID/OD (mm)	Mini bend radius (mm)	Max operating pressure (at 20°C (bar)	Colour
<b>PAMCL 27041000</b>	2.7 x 4	30	15	Clear
<b>PAMYW 27041000</b>	2.7 x 4	30	15	Yellow
<b>PAMBK 27041000</b>	2.7 x 4	30	15	Black
<b>PAMRD 27041000</b>	2.7 x 4	30	15	Red
<b>PAMGN 27041000</b>	2.7 x 4	30	15	Green
<b>PAMBE 04061000</b>	4 x 6	35	27	Blue
<b>PAMCL 04061000</b>	4 x 6	35	27	Clear
<b>PAMYW 04061000</b>	4 x 6	35	27	Yellow
<b>PAMBK 04061000</b>	4 x 6	35	27	Black
<b>PAMRD 04061000</b>	4 x 6	35	27	Red
<b>PAMGN 04061000</b>	4 x 6	35	27	Green

