

Polyamide tube in 300 meter-reel (unit of sales = 1 reel)



| | | | |
|---|---|--|------------------------------|
| <u>ID/OD (mm)</u> 8 x 10 | <u>Mini bend radius (mm)</u> 90 | <u>Max operating pressure (at 20°C) (bar)</u> 15 | <u>Colour</u> Blue |
| <u>Temperature</u> - 20°C to + 80°C | <u>Construction</u> Polyamide PA 12 | <u>Highlight</u> Excellent shape memory Highly resistant to chemicals | |

| Description | | | | |
|----------------------|------------|-----------------------|--|--------|
| Reference | ID/OD (mm) | Mini bend radius (mm) | Max operating pressure (at 20°C) (bar) | Colour |
| PAMBE 0810300 | 8 x 10 | 90 | 15 | Blue |
| PAMCL 0810300 | 8 x 10 | 90 | 15 | Clear |

| Reference | ID/OD (mm) | Mini bend radius (mm) | Max operating pressure (at 20°C) (bar) | Colour |
|--------------------------|------------|-----------------------|--|--------|
| PAMYW 0810300 | 8 x 10 | 90 | 15 | Yellow |
| PAMBK 0810300 | 8 x 10 | 90 | 15 | Black |
| PAMGN 0810300 | 8 x 10 | 90 | 15 | Green |
| PAMRD 0810300 | 8 x 10 | 90 | 15 | Red |

