

## AIRCA hose extension with metal safety quick couplers



<b>ID/OD (mm)</b> 16 x 25	<b>Length (m)</b> 10	<b>Profile</b> European 10.4 mm	<b>Coupler</b> ESI 11
<b>Adaptor</b> ERP 11	<b>Equipped with</b> Protector	<b>Operating pressure</b> 2 to 12 bar	<b>Temperature</b> -15°C to +70°C
<b>Construction</b> EPDM	<b>Highlight</b> Resistant to oils		

Description						
Reference	ID/OD (mm)	Length (m)	Profile	Coupler	Adaptor	Equipped with
<b>RAL AES1610</b>	16 x 25	10	European 10.4 mm	ESI 11	ERP 11	Protector
<b>RAL AES1620</b>	16 x 25	20	European 10.4 mm	ESI 11	ERP 11	Protector

Reference	ID/OD (mm)	Length (m)	Profile	Coupler	Adaptor	Equipped with
<b>RAL AES1910</b>	19 x 28	10	European 10.4 mm	ESI 11	ERP 11	Protector
<b>RAL AES1920</b>	19 x 28	20	European 10.4 mm	ESI 11	ERP 11	-
<b>RAL AIS1610</b>	16 x 25	10	ISO 6150 B	ISI 11	IRP 11	Protector
<b>RAL AIS1620</b>	16 x 25	20	ISO 6150 B	ISI 11	IRP 11	Protector
<b>RAL ACMB810</b>	8 x 15	10	ISO 6150 C	CSM 06	CRP 06	-
<b>RAL ACMB1010</b>	10 x 18	10	ISO 6150 C	CSM 06	CRP 06	-
<b>RAL ACM1310</b>	13 x 22	10	ISO 6150 C	CSM 08	CRP 08	Protector
<b>RAL ACM1610</b>	16 x 25	10	ISO 6150 C	CSM 11	CRP 11	Protector
<b>RAL ACM1620</b>	16 x 25	20	ISO 6150 C	CSM 11	CRP 11	Protector
<b>RAL ACM1910</b>	19 x 28	10	ISO 6150 C	CSM 11	CRP 11	Protector
<b>RAL ACM1920</b>	19 x 28	20	ISO 6150 C	CSM 11	CRP 11	-

