

## AIRCA hose extension with metal safety quick couplers



<p><b>ID/OD (mm)</b></p> <p>16 x 25</p>	<p><b>Length (m)</b></p> <p>10</p>	<p><b>Profile</b></p> <p>European 10.4 mm</p>	<p><b>Coupler</b></p> <p>ESI 11</p>
<p><b>Adaptor</b></p> <p>ERP 11</p>	<p><b>Equipped with</b></p> <p>Protector</p>	<p><b>Operating pressure</b></p> <p>2 to 12 bar</p>	<p><b>Temperature</b></p> <p>-15°C to +70°C</p>
<p><b>Construction</b></p> <p>EPDM</p>	<p><b>Highlight</b></p> <p>Resistant to oils</p>		

Description						
Reference	ID/OD (mm)	Length (m)	Profile	Coupler	Adaptor	Equipped with
<b>RAL AES1610</b>	16 x 25	10	European 10.4 mm	ESI 11	ERP 11	Protector
<b>RAL AES1620</b>	16 x 25	20	European 10.4 mm	ESI 11	ERP 11	Protector

Reference	ID/OD (mm)	Length (m)	Profile	Coupler	Adaptor	Equipped with
<b>RAL AES1910</b>	19 x 28	10	European 10.4 mm	ESI 11	ERP 11	Protector
<b>RAL AES1920</b>	19 x 28	20	European 10.4 mm	ESI 11	ERP 11	-
<b>RAL AIS1610</b>	16 x 25	10	ISO 6150 B	ISI 11	IRP 11	Protector
<b>RAL AIS1620</b>	16 x 25	20	ISO 6150 B	ISI 11	IRP 11	Protector
<b>RAL ACMB810</b>	8 x 15	10	ISO 6150 C	CSM 06	CRP 06	-
<b>RAL ACMB1010</b>	10 x 18	10	ISO 6150 C	CSM 06	CRP 06	-
<b>RAL ACM1310</b>	13 x 22	10	ISO 6150 C	CSM 08	CRP 08	Protector
<b>RAL ACM1610</b>	16 x 25	10	ISO 6150 C	CSM 11	CRP 11	Protector
<b>RAL ACM1620</b>	16 x 25	20	ISO 6150 C	CSM 11	CRP 11	Protector
<b>RAL ACM1910</b>	19 x 28	10	ISO 6150 C	CSM 11	CRP 11	Protector
<b>RAL ACM1920</b>	19 x 28	20	ISO 6150 C	CSM 11	CRP 11	-

