

AIRCA hose extension with metal safety quick couplers



| | | | |
|------------------------------|---------------------------------------|--|--------------------------------------|
| ID/OD (mm) 16 x 25 | Length (m) 10 | Profile European 10.4 mm | Coupler ESI 11 |
| Adaptor ERP 11 | Equipped with Protector | Operating pressure 2 to 12 bar | Temperature -15°C to +70°C |
| Construction EPDM | Highlight Resistant to oils | | |

| Description | | | | | | |
|------------------------|------------|------------|------------------|---------|---------|---------------|
| Reference | ID/OD (mm) | Length (m) | Profile | Coupler | Adaptor | Equipped with |
| RAL AES1610 | 16 x 25 | 10 | European 10.4 mm | ESI 11 | ERP 11 | Protector |
| RAL AES1620 | 16 x 25 | 20 | European 10.4 mm | ESI 11 | ERP 11 | Protector |

| Reference | ID/OD (mm) | Length (m) | Profile | Coupler | Adaptor | Equipped with |
|-------------------------|------------|------------|------------------|---------|---------|---------------|
| RAL AES1910 | 19 x 28 | 10 | European 10.4 mm | ESI 11 | ERP 11 | Protector |
| RAL AES1920 | 19 x 28 | 20 | European 10.4 mm | ESI 11 | ERP 11 | - |
| RAL AIS1610 | 16 x 25 | 10 | ISO 6150 B | ISI 11 | IRP 11 | Protector |
| RAL AIS1620 | 16 x 25 | 20 | ISO 6150 B | ISI 11 | IRP 11 | Protector |
| RAL ACMB810 | 8 x 15 | 10 | ISO 6150 C | CSM 06 | CRP 06 | - |
| RAL ACMB1010 | 10 x 18 | 10 | ISO 6150 C | CSM 06 | CRP 06 | - |
| RAL ACM1310 | 13 x 22 | 10 | ISO 6150 C | CSM 08 | CRP 08 | Protector |
| RAL ACM1610 | 16 x 25 | 10 | ISO 6150 C | CSM 11 | CRP 11 | Protector |
| RAL ACM1620 | 16 x 25 | 20 | ISO 6150 C | CSM 11 | CRP 11 | Protector |
| RAL ACM1910 | 19 x 28 | 10 | ISO 6150 C | CSM 11 | CRP 11 | Protector |
| RAL ACM1920 | 19 x 28 | 20 | ISO 6150 C | CSM 11 | CRP 11 | - |

