

AIRCA hose extension with metal safety quick couplers



<u>ID/OD (mm)</u> 16 x 25	<u>Length (m)</u> 10	<u>Profile</u> ISO 6150 B	<u>Coupler</u> ISI 11
<u>Adaptor</u> IRP 11	<u>Equipped with</u> Protector	<u>Operating pressure</u> 2 to 12 bar	<u>Temperature</u> -15°C to +70°C
<u>Construction</u> EPDM	<u>Highlight</u> Resistant to oils		

Description						
Reference	ID/OD (mm)	Length (m)	Profile	Coupler	Adaptor	Equipped with
RAL AES1610	16 x 25	10	European 10.4 mm	ESI 11	ERP 11	Protector
RAL AES1620	16 x 25	20	European 10.4 mm	ESI 11	ERP 11	Protector

Reference	ID/OD (mm)	Length (m)	Profile	Coupler	Adaptor	Equipped with
RAL AES1910	19 x 28	10	European 10.4 mm	ESI 11	ERP 11	Protector
RAL AES1920	19 x 28	20	European 10.4 mm	ESI 11	ERP 11	-
RAL AIS1610	16 x 25	10	ISO 6150 B	ISI 11	IRP 11	Protector
RAL AIS1620	16 x 25	20	ISO 6150 B	ISI 11	IRP 11	Protector
RAL ACMB810	8 x 15	10	ISO 6150 C	CSM 06	CRP 06	-
RAL ACMB1010	10 x 18	10	ISO 6150 C	CSM 06	CRP 06	-
RAL ACM1310	13 x 22	10	ISO 6150 C	CSM 08	CRP 08	Protector
RAL ACM1610	16 x 25	10	ISO 6150 C	CSM 11	CRP 11	Protector
RAL ACM1620	16 x 25	20	ISO 6150 C	CSM 11	CRP 11	Protector
RAL ACM1910	19 x 28	10	ISO 6150 C	CSM 11	CRP 11	Protector
RAL ACM1920	19 x 28	20	ISO 6150 C	CSM 11	CRP 11	-

