

STOFLEX anti-static rubber hose extension with prevoS1 safety quick couplers



ID/OD (mm) 8 x 15	Length (m) 10	Profile British	Coupler BSI 06
Adaptor BRP 06	Equipped with Protector	Operating pressure 2 to 12 bar	Temperature -15°C to +70°C

Description						
Reference	ID/OD (mm)	Length (m)	Profile	Coupler	Adaptor	Equipped with
RAL SBSB810	8 x 15	10	British	BSI 06	BRP 06	Protector
RAL SBSB1012	10 x 18	12.5	British	BSI 06	BRP 06	Protector
RAL SESB810	8 x 15	10	European 7.4 mm	ESI 07	ERP 07	Protector

Reference	ID/OD (mm)	Length (m)	Profile	Coupler	Adaptor	Equipped with
RAL SESB1012	10 x 18	12.5	European 7.4 mm	ESI 07	ERP 07	Protector
RAL SISB810	8 x 15	10	ISO 6150 B	ISI 06	IRP 06	Protector
RAL SISB1012	10 x 18	12.5	ISO 6150 B	ISI 06	IRP 06	Protector
RAL SCSB810	8 x 15	10	ISO 6150 C	CSI 06	CRP 06	Protector
RAL SCSB1012	10 x 18	12.5	ISO 6150 C	CSI 06	CRP 06	Protector
RAL SASB810	8 x 15	10	ARO 210	ASI 06	ARP 06	Protector
RAL SASB1012	10 x 18	12.5	ARO 210	ASI 06	ARP 06	Protector

