

STOFLEX anti-static rubber hose extension with prevoS1 safety quick couplers



<u>ID/OD (mm)</u> 8 x 15	<u>Length (m)</u> 10	<u>Profile</u> ISO 6150 B	<u>Coupler</u> ISI 06
<u>Adaptor</u> IRP 06	<u>Equipped with</u> Protector	<u>Operating pressure</u> 2 to 12 bar	<u>Temperature</u> -15°C to +70°C

Description						
Reference	ID/OD (mm)	Length (m)	Profile	Coupler	Adaptor	Equipped with
RAL SBSB810	8 x 15	10	British	BSI 06	BRP 06	Protector
RAL SBSB1012	10 x 18	12.5	British	BSI 06	BRP 06	Protector
RAL SESB810	8 x 15	10	European 7.4 mm	ESI 07	ERP 07	Protector

Reference	ID/OD (mm)	Length (m)	Profile	Coupler	Adaptor	Equipped with
RAL SESB1012	10 x 18	12.5	European 7.4 mm	ESI 07	ERP 07	Protector
RAL SISB810	8 x 15	10	ISO 6150 B	ISI 06	IRP 06	Protector
RAL SISB1012	10 x 18	12.5	ISO 6150 B	ISI 06	IRP 06	Protector
RAL SCSB810	8 x 15	10	ISO 6150 C	CSI 06	CRP 06	Protector
RAL SCSB1012	10 x 18	12.5	ISO 6150 C	CSI 06	CRP 06	Protector
RAL SASB810	8 x 15	10	ARO 210	ASI 06	ARP 06	Protector
RAL SASB1012	10 x 18	12.5	ARO 210	ASI 06	ARP 06	Protector

