

## AIRCA hose extension with prevoS1 swivel safety quick coupler



<b>ID/OD (mm)</b> 8 x 15	<b>Length (m)</b> 10	<b>Profile</b> British	<b>Coupler</b> BSI 06SW
<b>Adaptor</b> BRP 06	<b>Equipped with</b> Protector	<b>Operating pressure</b> 2 to 12 bar	<b>Temperature</b> -15°C to +70°C
<b>Construction</b> EPDM	<b>Highlight</b> Resistant to oils		

Description						
Reference	ID/OD (mm)	Length (m)	Profile	Coupler	Adaptor	Equipped with
<b>RAL ABSW810</b>	8 x 15	10	British	BSI 06SW	BRP 06	Protector
<b>RAL ABSW1010</b>	10 x 18	10	British	BSI 06SW	BRP 06	Protector

Reference	ID/OD (mm)	Length (m)	Profile	Coupler	Adaptor	Equipped with
<b>RAL AESW810</b>	8 x 15	10	European 10.4 mm	ESI 07SW	ERP 07	Protector
<b>RAL AESW1010</b>	10 x 18	10	European 10.4 mm	ESI 07SW	ERP 07	Protector
<b>RAL AESW1310</b>	13 x 22	10	European 10.4 mm	ESI 07SW	ERP 07	Protector
<b>RAL AISW810</b>	8 x 15	10	ISO 6150 B	ISI 06SW	IRP 06	Protector
<b>RAL AISW1010</b>	10 x 18	10	ISO 6150 B	ISI 06SW	IRP 06	Protector
<b>RAL AISW1310</b>	13 x 22	10	ISO 6150 B	ISI 08SW	IRP 06	Protector
<b>RAL ACSW810</b>	8 x 15	10	ISO 6150 C	CSI 06SW	CRP 06	Protector
<b>RAL ACSW1010</b>	10 x 18	10	ISO 6150 C	CSI 06SW	CRP 06	Protector
<b>RAL ACSW1310</b>	13 x 22	10	ISO 6150 C	CSI 08SW	CRP 08	-
<b>RAL AASW810</b>	8 x 15	10	ARO 210	ASI 06SW	ARP 06	Protector
<b>RAL AASW1010</b>	10 x 18	10	ARO 210	ASI 06SW	ARP 06	Protector

