

AIRCA hose extension with prevoS1 swivel safety quick coupler



ID/OD (mm) 8 x 15	Length (m) 10	Profile British	Coupler BSI 06SW
Adaptor BRP 06	Equipped with Protector	Operating pressure 2 to 12 bar	Temperature -15°C to +70°C
Construction EPDM	Highlight Resistant to oils		

Description						
Reference	ID/OD (mm)	Length (m)	Profile	Coupler	Adaptor	Equipped with
RAL ABSW810	8 x 15	10	British	BSI 06SW	BRP 06	Protector
RAL ABSW1010	10 x 18	10	British	BSI 06SW	BRP 06	Protector

Reference	ID/OD (mm)	Length (m)	Profile	Coupler	Adaptor	Equipped with
RAL AESW810	8 x 15	10	European 10.4 mm	ESI 07SW	ERP 07	Protector
RAL AESW1010	10 x 18	10	European 10.4 mm	ESI 07SW	ERP 07	Protector
RAL AESW1310	13 x 22	10	European 10.4 mm	ESI 07SW	ERP 07	Protector
RAL AISW810	8 x 15	10	ISO 6150 B	ISI 06SW	IRP 06	Protector
RAL AISW1010	10 x 18	10	ISO 6150 B	ISI 06SW	IRP 06	Protector
RAL AISW1310	13 x 22	10	ISO 6150 B	ISI 08SW	IRP 06	Protector
RAL ACSW810	8 x 15	10	ISO 6150 C	CSI 06SW	CRP 06	Protector
RAL ACSW1010	10 x 18	10	ISO 6150 C	CSI 06SW	CRP 06	Protector
RAL ACSW1310	13 x 22	10	ISO 6150 C	CSI 08SW	CRP 08	-
RAL AASW810	8 x 15	10	ARO 210	ASI 06SW	ARP 06	Protector
RAL AASW1010	10 x 18	10	ARO 210	ASI 06SW	ARP 06	Protector

