

STOFLEX anti-static rubber hose extension and prevoS1 swivel safety quick coupler



| | | | |
|-----------------------------|-----------------------------------|--|--------------------------------------|
| ID/OD (mm) 8 x 15 | Length (m) 10 | Profile British | Coupler BSI 06SW |
| Adaptor BRP 06 | Equipped with Protector | Operating pressure 2 to 12 bar | Temperature -15°C to +70°C |

| Description | | | | | | |
|---------------------|------------|------------|-----------------|----------|---------|---------------|
| Reference | ID/OD (mm) | Length (m) | Profile | Coupler | Adaptor | Equipped with |
| RAL SBSW810 | 8 x 15 | 10 | British | BSI 06SW | BRP 06 | Protector |
| RAL SBSW1012 | 10 x 18 | 12.5 | British | BSI 06SW | BRP 06 | Protector |
| RAL SESW810 | 8 x 15 | 10 | European 7.4 mm | ESI 07SW | ERP 07 | Protector |

| Reference | ID/OD (mm) | Length (m) | Profile | Coupler | Adaptor | Equipped with |
|-------------------------|------------|------------|--------------------|----------|---------|---------------|
| RAL SESW1012 | 10 x 18 | 12.5 | European 7.4 mm | ESI 07SW | ERP 07 | Protector |
| RAL SISW810 | 8 x 15 | 10 | ISO 6150 B | ISI 06SW | IRP 06 | Protector |
| RAL SISW1012 | 10 x 18 | 12.5 | ISO 6150 B | ISI 06SW | IRP 06 | Protector |
| RAL SCSW810 | 8 x 15 | 10 | ISO 6150 C | CSI 06SW | CRP 06 | Protector |
| RAL SCSW1012 | 10 x 18 | 12.5 | ISO 6150 C | CSI 06SW | CRP 06 | Protector |
| RAL SASW810 | 8 x 15 | 10 | ARO 210 | ASI 06SW | ARP 06 | Protector |
| RAL SASW1012 | 10 x 18 | 12.5 | ARO 210 | ASI 06SW | ARP 06 | Protector |

