

# STOFLEX anti-static rubber hose extension and prevoS1 swivel safety quick coupler



<b>ID/OD (mm)</b> 8 x 15	<b>Length (m)</b> 10	<b>Profile</b> European 7.4 mm	<b>Coupler</b> ESI 07SW
<b>Adaptor</b> ERP 07	<b>Equipped with</b> Protector	<b>Operating pressure</b> 2 to 12 bar	<b>Temperature</b> -15°C to +70°C

Description						
Reference	ID/OD (mm)	Length (m)	Profile	Coupler	Adaptor	Equipped with
<b>RAL SBSW810</b>	8 x 15	10	British	BSI 06SW	BRP 06	Protector
<b>RAL SBSW1012</b>	10 x 18	12.5	British	BSI 06SW	BRP 06	Protector
<b>RAL SESW810</b>	8 x 15	10	European 7.4 mm	ESI 07SW	ERP 07	Protector

Reference	ID/OD (mm)	Length (m)	Profile	Coupler	Adaptor	Equipped with
<b>RAL SESW1012</b>	10 x 18	12.5	European 7.4 mm	ESI 07SW	ERP 07	Protector
<b>RAL SISW810</b>	8 x 15	10	ISO 6150 B	ISI 06SW	IRP 06	Protector
<b>RAL SISW1012</b>	10 x 18	12.5	ISO 6150 B	ISI 06SW	IRP 06	Protector
<b>RAL SCSW810</b>	8 x 15	10	ISO 6150 C	CSI 06SW	CRP 06	Protector
<b>RAL SCSW1012</b>	10 x 18	12.5	ISO 6150 C	CSI 06SW	CRP 06	Protector
<b>RAL SASW810</b>	8 x 15	10	ARO 210	ASI 06SW	ARP 06	Protector
<b>RAL SASW1012</b>	10 x 18	12.5	ARO 210	ASI 06SW	ARP 06	Protector

