

STOFLEX anti-static rubber hose extension and prevoS1 swivel safety quick coupler



ID/OD (mm) 8 x 15	Length (m) 10	Profile ISO 6150 B	Coupler ISI 06SW
Adaptor IRP 06	Equipped with Protector	Operating pressure 2 to 12 bar	Temperature -15°C to +70°C

Description						
Reference	ID/OD (mm)	Length (m)	Profile	Coupler	Adaptor	Equipped with
RAL SBSW810	8 x 15	10	British	BSI 06SW	BRP 06	Protector
RAL SBSW1012	10 x 18	12.5	British	BSI 06SW	BRP 06	Protector
RAL SESW810	8 x 15	10	European 7.4 mm	ESI 07SW	ERP 07	Protector

Reference	ID/OD (mm)	Length (m)	Profile	Coupler	Adaptor	Equipped with
RAL SESW1012	10 x 18	12.5	European 7.4 mm	ESI 07SW	ERP 07	Protector
RAL SISW810	8 x 15	10	ISO 6150 B	ISI 06SW	IRP 06	Protector
RAL SISW1012	10 x 18	12.5	ISO 6150 B	ISI 06SW	IRP 06	Protector
RAL SCSW810	8 x 15	10	ISO 6150 C	CSI 06SW	CRP 06	Protector
RAL SCSW1012	10 x 18	12.5	ISO 6150 C	CSI 06SW	CRP 06	Protector
RAL SASW810	8 x 15	10	ARO 210	ASI 06SW	ARP 06	Protector
RAL SASW1012	10 x 18	12.5	ARO 210	ASI 06SW	ARP 06	Protector

