

## DIFLEX PVC hose extension with prevoS1 safety quick couplers



<b><u>ID/OD (mm)</u></b> 8 x 14	<b><u>Length (m)</u></b> 10	<b><u>Profile</u></b> British	<b><u>Coupler</u></b> BSI 06
<b><u>Adaptor</u></b> BRP 06	<b><u>Equipped with</u></b> Protector	<b><u>Operating pressure</u></b> 2 to 12 bar	<b><u>Temperature</u></b> -15°C to +60°C
<b><u>Construction</u></b> PVC	<b><u>Equipped with</u></b> Coupler and adaptor		

Description						
Reference	ID/OD (mm)	Length (m)	Profile	Coupler	Adaptor	Equipped with
<b>RAL DBSB810</b>	8 x 14	10	British	BSI 06	BRP 06	Protector
<b>RAL DESB810</b>	8 x 14	10	European 7.4 mm	ESI 07	ERP 07	Protector

Reference	ID/OD (mm)	Length (m)	Profile	Coupler	Adaptor	Equipped with
<b>RAL DISB810</b>	8 x 14	10	ISO 6150 B	ISI 06	IRP 06	Protector
<b>RAL DCSB810</b>	8 x 14	10	ISO 6150 C	CSI 06	CRP 06	Protector
<b>RAL DASB810</b>	8 x 14	10	ARO 210	ASI 06	ARP 06	Protector

