

FLEXAIR high flexibility hybrid polymer hose extension with prevoS1 safety quick couplers



ID/OD (mm) 8 x 12,5	Length (m) 13	Profile British	Coupler BSI 06
Adaptor BRP 06	Equipped with Protector	Operating pressure 2 to 12 bar	Temperature -15°C to +60°C
Construction PVC	Equipped with Coupler and adaptor		

Description						
Reference	ID/OD (mm)	Length (m)	Profile	Coupler	Adaptor	Equipped with
RAL RBSB0810	8 x 12,5	13	British	BSI 06	BRP 06	Protector

Reference	ID/OD (mm)	Length (m)	Profile	Coupler	Adaptor	Equipped with
RAL RBSB0820	8 x 12,5	14	British	BSI 06	BRP 06	Protector
RAL RBSB1010	10 x 15,5	10	British	BSI 06	BRP 06	Protector
RAL RBSB1020	10 x 15,5	16	British	BSI 06	BRP 06	Protector
RAL RESB0810	8 x 12,5	10	European 7,4	ESI 07	ERP 07	Protector
RAL RESB0820	8 x 12,5	20	European 7,4	ESI 07	ERP 07	Protector
RAL RESB1010	10 x 15,5	10	European 7.4	ESI 07	ERP 07	Protector
RAL RESB1020	10 x 15,5	20	European 7,4	ESI 07	ERP 07	Protector
RAL RESB1320	13 x 19	20	European 7,4	ESI 07	ERP 07	Protector
RAL RESEB1320	13 x 19	20	European 10,4	ESI 11EB	ERP 11	Protecteur
RAL RCSB0810	8 x 12,5	10	ISO 6150 C	CSI 06	CRP 06	Protector
RAL RCSB0820	8 x 12,5	20	ISO 6150 C	CSI 06	CRP 06	Protector
RAL RCSB1010	10 x 15,5	10	ISO 6150 C	CSI 06	CRP 06	Protector
RAL RCSB1020	10 x 15,5	20	ISO 6150 C	CSI 06	CRP 06	Protector

Reference	ID/OD (mm)	Length (m)	Profile	Coupler	Adaptor	Equipped with
RAL RCSB1320	13 x 19	20	ISO 6150 C	CSI 08	CRP 06	Protector

