

Hoses with swaged ferrules



| | | | |
|--|--|--|---|
| <u>BSPF female thread</u> G 3/8 | <u>Diameter (mm)</u> 10 x 16 | <u>Length (m)</u> 10 | <u>Bend radius (at 20°C - mm)</u> 40 |
| <u>Max operating pressure (bar)</u> 10 | <u>Weight (g/m)</u> 156 | <u>Max operating pressure</u> 10 bar | <u>Temperature</u> -20°C to +60°C |
| <u>Construction</u> PVC | | | |

| Description | | | | | | |
|-----------------|--------------------|---------------|------------|-----------------------------|------------------------------|--------------|
| Reference | BSPF female thread | Diameter (mm) | Length (m) | Bend radius (at 20°C - mm) | Max operating pressure (bar) | Weight (g/m) |
| BAH 1010 | G 3/8 | 10 x 16 | 10 | 40 | 10 | 156 |
| BAH 1015 | G 3/8 | 10 x 16 | 15 | 40 | 10 | 156 |

| Reference | BSPP female thread | Diameter (mm) | Length (m) | Bend radius (at 20°C - mm) | Max operating pressure (bar) | Weight(g/m) |
|-----------------|--------------------|---------------|------------|-----------------------------|------------------------------|-------------|
| BAH 1020 | G 3/8 | 10 x 16 | 20 | 40 | 10 | 156 |

