


Polyurethane recoils with rigid and swiveling male fittings



Blue.

Teflon-coated coupler.

<u>BSPT male thread</u> R 1/4	<u>ID/OD (mm)</u> 5 x 8	<u>Coil Ø (mm)</u> 42	<u>Max length (m)</u> 2
<u>Min. length (m)</u> 0.18	<u>Max operating pressure</u> 8 bar	<u>Temperature</u> -15°C to +70°C	<u>Construction</u> Polyurethane
<u>Highlight</u> Non scratch			

Description					
Reference	BSPT male thread	ID/OD (mm)	Coil Ø (mm)	Max length (m)	Min. length (m)
PUS 52	R 1/4	5 x 8	42	2	0.18
PUS 54	R 1/4	5 x 8	42	4	0.4
PUS 56	R 1/4	5 x 8	42	6	0.6
PUS 58	R 1/4	5 x 8	42	8	0.80

Reference	BSPT male thread	ID/OD (mm)	Coil Ø (mm)	Max length (m)	Min. length (m)
PUS 64	R 1/4	6.5 x 10	52	4	0.4
PUS 66	R 1/4	6.5 x 10	52	6	0.55
PUS 68	R 1/4	6.5 x 10	52	8	0.8
PUS 610	R 1/4	6.5 x 10	52	10	0.95
PUS 84	R 3/8	8 x 12	65	4	0.4
PUS 86	R 3/8	8 x 12	65	6	0.65
PUS 88	R 3/8	8 x 12	65	8	0.72
PUS 815	R 3/8	8 x 12	65	15	1.35

