

Polyamide recoils with swiveling male fittings



<u>BSPB male thread</u> G 1/4	<u>ID/OD (mm)</u> 6 x 8	<u>Coil Ø (mm)</u> 96	<u>Max length (m)</u> 2.5
<u>Min. length (m)</u> 0.12	<u>Max operating pressure</u> 10 bar	<u>Temperature</u> -20°C to +90°C	<u>Construction</u> Polyamide PA 12
<u>Highlight</u> Highly resistant to chemicals			

Description					
Reference	BSPB male thread	ID/OD (mm)	Coil Ø (mm)	Max length (m)	Min. length (m)
SPIC 62	G 1/4	6 x 8	96	2.5	0.12
SPIC 65	G 1/4	6 x 8	96	5	0.24
SPIC 610	G 1/4	6 x 8	96	10	0.48
SPIC 620	G 1/4	6 x 8	96	20	0.96
SPIC 82	G 1/4	8 x 10	110	2.5	0.14
SPIC 85	G 1/4	8 x 10	110	5	0.28
SPIC 810	G 1/4	8 x 10	110	10	0.55
SPIC 820	G 1/4	8 x 10	110	20	1.1

Reference	BSPP male thread	ID/OD (mm)	Coil Ø (mm)	Max length (m)	Min. length (m)
SPIC 102	G 3/8	9.5 x 12	144	2.5	0.12
SPIC 104	G 3/8	9.5 x 12	144	4	0.24
SPIC 108	G 3/8	9.5 x 12	144	8.5	0.49
SPIC 1016	G 3/8	9.5 x 12	144	17	0.97

Dimensions

Reference

SPIC 62

SPIC 65

SPIC 610

SPIC 620

SPIC 82

SPIC 85

SPIC 810

SPIC 820

SPIC 102

SPIC 104

SPIC 108

SPIC 1016