

## Polyamide recoils with swiveling male fittings



<u><b>BSPB male thread</b></u> G 1/4	<u><b>ID/OD (mm)</b></u> 6 x 8	<u><b>Coil Ø (mm)</b></u> 96	<u><b>Max length (m)</b></u> 2.5
<u><b>Min. length (m)</b></u> 0.12	<u><b>Max operating pressure</b></u> 10 bar	<u><b>Temperature</b></u> -20°C to +90°C	<u><b>Construction</b></u> Polyamide PA 12
<u><b>Highlight</b></u> Highly resistant to chemicals			

Description					
Reference	BSPB male thread	ID/OD (mm)	Coil Ø (mm)	Max length (m)	Min. length (m)
<b>SPIC 62</b>	G 1/4	6 x 8	96	2.5	0.12
<b>SPIC 65</b>	G 1/4	6 x 8	96	5	0.24
<b>SPIC 610</b>	G 1/4	6 x 8	96	10	0.48
<b>SPIC 620</b>	G 1/4	6 x 8	96	20	0.96
<b>SPIC 82</b>	G 1/4	8 x 10	110	2.5	0.14
<b>SPIC 85</b>	G 1/4	8 x 10	110	5	0.28
<b>SPIC 810</b>	G 1/4	8 x 10	110	10	0.55
<b>SPIC 820</b>	G 1/4	8 x 10	110	20	1.1

Reference	BSPP male thread	ID/OD (mm)	Coil Ø (mm)	Max length (m)	Min. length (m)
<b>SPIC 102</b>	G 3/8	9.5 x 12	144	2.5	0.12
<b>SPIC 104</b>	G 3/8	9.5 x 12	144	4	0.24
<b>SPIC 108</b>	G 3/8	9.5 x 12	144	8.5	0.49
<b>SPIC 1016</b>	G 3/8	9.5 x 12	144	17	0.97

Dimensions	
	Reference
	<b>SPIC 62</b>
	<b>SPIC 65</b>
	<b>SPIC 610</b>
	<b>SPIC 620</b>
	<b>SPIC 82</b>
	<b>SPIC 85</b>
	<b>SPIC 810</b>
	<b>SPIC 820</b>
	<b>SPIC 102</b>
	<b>SPIC 104</b>
	<b>SPIC 108</b>
	<b>SPIC 1016</b>