

Polyamide recoils without fittings



<u>ID/OD (mm)</u> 2.7 x 4	<u>Coil Ø (mm)</u> 28	<u>Max length (m)</u> 10	<u>Min. length (m)</u> 1.06
<u>Max operating pressure</u> 10 bar	<u>Temperature</u> -20°C to +90°C	<u>Construction</u> Polyamide PA 12	<u>Highlight</u> Highly resistant to chemicals

Description				
Reference	ID/OD (mm)	Coil Ø (mm)	Max length (m)	Min. length (m)
SPIR 2710	2.7 x 4	28	10	1.06
SPIR 456	4.5 x 6	52	9	1
SPIR 4526	4 x 6	72	26	1.33
SPIR 610	6 x 8	96	10	0.48
SPIR 620	6 x 8	96	20	0.96
SPIR 820	8 x 10	110	20	1.1
SPIR 1016	9.5 x 12	144	17	0.97
SPIR 12730	12.7 x 16	222	24	1.33

Reference	ID/OD (mm)	Coil Ø (mm)	Max length (m)	Min. length (m)
SPIR 1630	16 x 20	230	20	1.33

Dimensions	
	Reference
	SPIR 2710
	SPIR 456
	SPIR 4526
	SPIR 610
	SPIR 620
	SPIR 820
	SPIR 1016
	SPIR 12730
	SPIR 1630