

# DMO - DGO series - High pressure stainless steel - HP reinforced rubber hose



<p><b><u>Outlet</u></b> G 3/8 + M22 x 1.5 on high pressure hose reel</p>	<p><b><u>Swivel inlet (BSPP)</u></b> G 3/8 + M22 x 1.5 on hot water machine</p>	<p><b><u>ID/OD (mm)</u></b> 8 x 15</p>	<p><b><u>Length (m)</u></b> 3</p>
<p><b><u>Weight (kg)</u></b> 1.3</p>	<p><b><u>Technology</u></b> Pipe locked with ratchet stop</p>	<p><b><u>Max operating pressure</u></b> 400 bar</p>	<p><b><u>Temperature</u></b> -40°C to +150°C</p>
<p><b><u>Equipped with</u></b> Fixed bracket</p>			

Description					
Reference	Outlet	Swivel inlet (BSPP)	ID/OD (mm)	Length (m)	Weight (kg)

<b>DMG KITHP3</b>	G 3/8 + M22 x 1.5 on high pressure hose reel	G 3/8 + M22 x 1.5 on hot water machine	8 x 15	3	1.3
<b>DMG KITHP6</b>	G 3/8 + M22 x 1.5 on high pressure hose reel	G 3/8 + M22 x 1.5 on hot water machine	8 x 15	6	2.7

