


## Female thread coupler



|   |   |   |  |
|---|---|---|--|
| <p><b><u>BSPF female thread</u></b><br/>G 1/4</p>       | <p><b><u>BSPT female thread</u></b><br/>-</p> | <p><b><u>Profile</u></b><br/>Asian</p>              | <p><b><u>Technology</u></b><br/>Sleeve</p>           |
| <p><b><u>Operating pressure</u></b><br/>2 to 12 bar</p> | <p><b><u>ID Passage</u></b><br/>8 mm</p>      | <p><b><u>Temperature</u></b><br/>-15°C to +70°C</p> | <p><b><u>Construction</u></b><br/>Composite body</p> |
| <p><b><u>Highlight</u></b><br/>Non scratch</p>          |   |   |  |

| Description       |                    |                    |
|-------------------|--------------------|--------------------|
| Reference         | BSPF female thread | BSPT female thread |
| <b>ORG 081101</b> | G 1/4              | -                  |
| <b>ORG 081102</b> | G 3/8              | -                  |
| <b>ORG 081103</b> | G 1/2              | -                  |
| <b>ORG 081112</b> | -                  | R 3/8              |
| <b>ORG 081113</b> | -                  | R 1/2              |



### Dimensions

| Reference         | A mm | B mm | C mm |
|-------------------|------|------|------|
| <b>ORG 081101</b> | 54   | 33   | 27   |
| <b>ORG 081102</b> | 55   | 33   | 27   |
| <b>ORG 081103</b> | 60   | 33   | 27   |
| <b>ORG 081112</b> | 55   | 33   | 27   |
| <b>ORG 081113</b> | 60   | 33   | 27   |