

Options



<p>Description</p> <p>(1) Metal cover diam.280 mm</p>	<p>Technology</p> <p>Piston dual action</p>	<p>Operating pressure</p> <p>3 to 7 bar</p>	<p>Outlet pressure</p> <p>406 bar (air pressure at 7 bar)</p>
<p>Flow rate</p> <p>900 g/min (for air pressure 6 bar)</p>	<p>BSPP female thread</p> <p>Air inlet : G 1/4</p>	<p>Pressure ratio</p> <p>58:1</p>	<p>BSPP male thread</p> <p>Grease outlet : G 1/4</p>

Description	
Reference	Description
EPG CV20	(1) Metal cover diam.280 mm

Reference	Description
EPG CV30	(1) Metal cover diam. 320 mm
EPG CV60	(1) Metal cover diam. 385 mm
EPG CV65	(1) Metal cover Ø 380 to 410 mm
EPG MB20	(2) Sealing diaphragm Ø 240/260mm
EPG MB30	(2) Sealing diaphragm Ø 270/290 mm for EPG KR30
EPG MB34	(2) Sealing diaphragm Ø 300/330 mm
EPG MB60	(2) Sealing diaphragm Ø 335/360 mm for EPG KR60
EPG MB65	(2) Sealing diaphragm Ø 370/400mm
EPG TC414	(3) Rubber hose 4 m
EPG TC614	(3) Rubber hose 6 m
EPG TC214	(3) Rubber hose for connecting pump to reel
EPG RT14	Sealing coupling
EPG SW14	(4) Universal joint sealing coupling
EPG PG	Carrying handle
EPG VS30	(5) 30 mm bolt to hold pump in drum
EPG CA20	(6) Transport cart for 12/20 kg drums
EPG CAN60	(6) Transport cart for 20/60 kg

