

Flexible hose



ID/OD (mm) 10 x 18	Length (m) 0,4	Thread R 1/4	Adaptor BRP 06
Profile British	Operating pressure 2 to 12 bar	Temperature -15°C to +70°C	Construction EPDM
Applications Power supply for pneumatic tools	Highlight Resistant to oils		

Description					
Reference	ID/OD (mm)	Length (m)	Thread	Adaptor	Profile
MAB 061410	10 x 18	0,4	R 1/4	BRP 06	British
MAE 071410	10 x 18	0,4	R 1/4	ERP 07	European 7.4 mm
MAE 073813	13 x 22	0,4	R 3/8	ERP 07	European 7.4 mm
MAI 061410	10 x 18	0,4	R 1/4	IRP 06	ISO 6150B
MAI 061210	10 x 18	0,4	R 1/2	IRP 06	ISO 6150B
MAI 083813	13 x 22	0,4	R 3/8	IRP 08	ISO 6150B

Reference	ID/OD (mm)	Length (m)	Thread	Adaptor	Profile
MAI 081213	13 x 22	0.4	R 1/2	IRP 08	ISO 6150B
MAI 111216	16 x 25	0.4	R 1/2	IRP 11	ISO 6150B
MAI 113416	16 x 25	0.4	R 3/4	IRP 11	ISO 6150B
MAC 061410	10 x 18	0.4	R 1/4	CRP 06	ISO 6150C
MAC 083813	13 x 22	0.4	R 3/8	CRP 08	ISO 6150C
MAO 061410	10 x 18	0.4	R 1/4	ORP 08	Asian
MAA 061410	10 x 18	0.4	R 1/4	ARP 06	ARO 210

