

## Flexible hose



<p><b>ID/OD (mm)</b></p> <p>10 x 18</p>	<p><b>Length (m)</b></p> <p>0,4</p>	<p><b>Thread</b></p> <p>R 1/4</p>	<p><b>Adaptor</b></p> <p>BRP 06</p>
<p><b>Profile</b></p> <p>British</p>	<p><b>Operating pressure</b></p> <p>2 to 12 bar</p>	<p><b>Temperature</b></p> <p>-15°C to +70°C</p>	<p><b>Construction</b></p> <p>EPDM</p>
<p><b>Applications</b></p> <p>Power supply for pneumatic tools</p>	<p><b>Highlight</b></p> <p>Resistant to oils</p>		

Description					
Reference	ID/OD (mm)	Length (m)	Thread	Adaptor	Profile
<b>MAB 061410</b>	10 x 18	0,4	R 1/4	BRP 06	British
<b>MAE 071410</b>	10 x 18	0,4	R 1/4	ERP 07	European 7.4 mm
<b>MAE 073813</b>	13 x 22	0,4	R 3/8	ERP 07	European 7.4 mm
<b>MAI 061410</b>	10 x 18	0,4	R 1/4	IRP 06	ISO 6150B
<b>MAI 061210</b>	10 x 18	0,4	R 1/2	IRP 06	ISO 6150B
<b>MAI 083813</b>	13 x 22	0,4	R 3/8	IRP 08	ISO 6150B

Reference	ID/OD (mm)	Length (m)	Thread	Adaptor	Profile
<b>MAI 081213</b>	13 x 22	0.4	R 1/2	IRP 08	ISO 6150B
<b>MAI 111216</b>	16 x 25	0.4	R 1/2	IRP 11	ISO 6150B
<b>MAI 113416</b>	16 x 25	0.4	R 3/4	IRP 11	ISO 6150B
<b>MAC 061410</b>	10 x 18	0.4	R 1/4	CRP 06	ISO 6150C
<b>MAC 083813</b>	13 x 22	0.4	R 3/8	CRP 08	ISO 6150C
<b>MAO 061410</b>	10 x 18	0.4	R 1/4	ORP 08	Asian
<b>MAA 061410</b>	10 x 18	0.4	R 1/4	ARP 06	ARO 210

