

## Flexible hose



<b>ID/OD (mm)</b> 10 x 18	<b>Length (m)</b> 0,4	<b>Thread</b> R 1/4	<b>Adaptor</b> BRP 06
<b>Profile</b> British	<b>Operating pressure</b> 2 to 12 bar	<b>Temperature</b> -15°C to +70°C	<b>Construction</b> EPDM
<b>Applications</b> Power supply for pneumatic tools	<b>Highlight</b> Resistant to oils		

Description					
Reference	ID/OD (mm)	Length (m)	Thread	Adaptor	Profile
<b>MAB 061410</b>	10 x 18	0,4	R 1/4	BRP 06	British
<b>MAE 071410</b>	10 x 18	0,4	R 1/4	ERP 07	European 7.4 mm
<b>MAE 073813</b>	13 x 22	0,4	R 3/8	ERP 07	European 7.4 mm
<b>MAI 061410</b>	10 x 18	0,4	R 1/4	IRP 06	ISO 6150B
<b>MAI 061210</b>	10 x 18	0,4	R 1/2	IRP 06	ISO 6150B
<b>MAI 083813</b>	13 x 22	0,4	R 3/8	IRP 08	ISO 6150B

Reference	ID/OD (mm)	Length (m)	Thread	Adaptor	Profile
<b>MAI 081213</b>	13 x 22	0.4	R 1/2	IRP 08	ISO 6150B
<b>MAI 111216</b>	16 x 25	0.4	R 1/2	IRP 11	ISO 6150B
<b>MAI 113416</b>	16 x 25	0.4	R 3/4	IRP 11	ISO 6150B
<b>MAC 061410</b>	10 x 18	0.4	R 1/4	CRP 06	ISO 6150C
<b>MAC 083813</b>	13 x 22	0.4	R 3/8	CRP 08	ISO 6150C
<b>MAO 061410</b>	10 x 18	0.4	R 1/4	ORP 08	Asian
<b>MAA 061410</b>	10 x 18	0.4	R 1/4	ARP 06	ARO 210

