

## Polyurethane recoils with prevoS1 safety release quick couplers



<p><b>ID/OD (mm)</b></p> <p>5 x 8</p>	<p><b>Profile</b></p> <p>European 7.4 mm</p>	<p><b>Coupler</b></p> <p>ESI 07</p>	<p><b>Max length (m)</b></p> <p>2</p>
<p><b>Max operating pressure</b></p> <p>8 bar</p>	<p><b>Temperature</b></p> <p>-15°C to +70°C</p>	<p><b>Construction</b></p> <p>Polyurethane</p>	<p><b>Highlight</b></p> <p>Excellent shape memory</p>
<p><b>Equipped with</b></p> <p>Swivel fitting</p>			

Description				
Reference	ID/OD (mm)	Profile	Coupler	Max length (m)
<b>PUS 52ES</b>	5 x 8	European 7.4 mm	ESI 07	2
<b>PUS 54ES</b>	5 x 8	European 7.4 mm	ESI 07	4

Reference	ID/OD (mm)	Profile	Coupler	Max length (m)
<b>PUS 64ES</b>	6.5 x 10	European 7.4 mm	ESI 07	4
<b>PUS 66ES</b>	6.5 x 10	European 7.4 mm	ESI 07	6
<b>PUS 68ES</b>	6.5 x 10	European 7.4 mm	ESI 07	8
<b>PUS 84ES</b>	8 x 12	European 7.4 mm	ESI 07	4
<b>PUS 86ES</b>	8 x 12	European 7.4 mm	ESI 07	6
<b>PUS 88ES</b>	8 x 12	European 7.4 mm	ESI 07	8

