

Polyurethane recoils with prevoS1 safety release quick couplers



<p>ID/OD (mm)</p> <p>5 x 8</p>	<p>Profile</p> <p>European 7.4 mm</p>	<p>Coupler</p> <p>ESI 07</p>	<p>Max length (m)</p> <p>2</p>
<p>Max operating pressure</p> <p>8 bar</p>	<p>Temperature</p> <p>-15°C to +70°C</p>	<p>Construction</p> <p>Polyurethane</p>	<p>Highlight</p> <p>Excellent shape memory</p>
<p>Equipped with</p> <p>Swivel fitting</p>			

Description				
Reference	ID/OD (mm)	Profile	Coupler	Max length (m)
PUS 52ES	5 x 8	European 7.4 mm	ESI 07	2
PUS 54ES	5 x 8	European 7.4 mm	ESI 07	4

Reference	ID/OD (mm)	Profile	Coupler	Max length (m)
PUS 64ES	6.5 x 10	European 7.4 mm	ESI 07	4
PUS 66ES	6.5 x 10	European 7.4 mm	ESI 07	6
PUS 68ES	6.5 x 10	European 7.4 mm	ESI 07	8
PUS 84ES	8 x 12	European 7.4 mm	ESI 07	4
PUS 86ES	8 x 12	European 7.4 mm	ESI 07	6
PUS 88ES	8 x 12	European 7.4 mm	ESI 07	8

