

Polyurethane tube Ester base in 100 meter-reel (unit of sales = 1 reel)



<u>ID/OD (mm)</u> 2.5 x 4	<u>Mini bend radius (mm)</u> 12	<u>Max operating pressure (at 20°C (bar))</u> 10	<u>Colour</u> Black
<u>Temperature</u> - 20°C to +70°C	<u>Construction</u> Polyurethane Ester base	<u>Highlight</u> Resistant to oils and greases	

Description				
Reference	ID/OD (mm)	Mini bend radius (mm)	Max operating pressure (at 20°C (bar))	Colour
PUBK M2504100	2.5 x 4	12	10	Black
PUBE M2504100	2.5 x 4	12	10	Blue

Reference	ID/OD (mm)	Mini bend radius (mm)	Max operating pressure (at 20°C (bar)	Colour
PUCR M2504100	2.5 x 4	12	10	Clear
PUGN M2504100	2.5 x 4	12	10	Green
PUYW M2504100	2.5 x 4	12	10	Yellow
PUGY M2504100	2.5 x 4	12	10	Grey
PURD M2504100	2.5 x 4	12	10	Red
PUBK M0406100	4 x 6	15	9	Black
PUBE M0406100	4 x 6	15	9	Blue
PUCR M0406100	4 x 6	15	9	Clear
PUGN M0406100	4 x 6	15	9	Green
PUYW M0406100	4 x 6	15	9	Yellow
PUGY M0406100	4 x 6	15	9	Grey
PURD M0406100	4 x 6	15	9	Red
PUBK M5508100	5.5 x 8	20	8.5	Black
PUBE M5508100	5.5 x 8	20	8.5	Blue
PUCR M5508100	5.5 x 8	20	8.5	Clear
PUGN M5508100	5.5 x 8	20	8.5	Green
PUYW M5508100	5.5 x 8	20	8.5	Yellow
PUGY M5508100	5.5 x 8	20	8.5	Grey
PURD M5508100	5.5 x 8	20	8.5	Red
PUBK M0710100	7 x 10	25	8.5	Black

Reference	ID/OD (mm)	Mini bend radius (mm)	Max operating pressure (at 20°C (bar)	Colour
PUBE M0710100	7 x 10	25	8.5	Blue
PUCR M0710100	7 x 10	25	8.5	Clear
PUBK M0812100	8 x 12	35	9	Black
PUBE M0812100	8 x 12	35	9	Blue
PUCR M0812100	8 x 12	35	9	Clear
PUBK M9514100	9.5 x 14	45	9	Black

