

## Connection hoses - Female swivel connections



<b><u>BSPB female thread</u></b> G 3/8	<b><u>Length (m)</u></b> 1.5	<b><u>Bend radius (at 20°C)(mm)</u></b> 130	<b><u>Max operating pressure (bar)</u></b> 180
<b><u>Temperature (°C)</u></b> -40 to +110	<b><u>Construction</u></b> Rubber with metallic braiding	<b><u>Highlight</u></b> Resistant to oils, abrasion and ozone	<b><u>Equipped with</u></b> Rotating coupling

Description					
Reference	BSPB female thread	Length (m)	Bend radius (at 20°C)(mm)	Max operating pressure (bar)	Temperature (°C)
<b>LEF 17</b>	G 3/8	1.5	130	180	-40 to +110
<b>LEF 21</b>	G 1/2	1.5	130	160	-40 to +110
<b>LEF 27</b>	G 3/4	1.5	240	105	-40 to +110
<b>LEF 34</b>	G 1	1.5	300	88	-40 to +110
<b>LEF 42</b>	G 1 1/4	2.2	420	63	-40 to +110
<b>LEF 49</b>	G 1 1/2	2.5	500	50	-40 to +110

Reference	BSPP female thread	Length (m)	Bend radius(at 20°C)(mm)	Max operating pressure (bar)	Temperature (°C)
<b>LEF 60</b>	G 2	2	630	80	-40 to +110

