

Polyurethane tube Ether base in 100 meter-reel (unit of sales = 1 reel)



<u>ID/OD (mm)</u> 2.5 x 4	<u>Mini bend radius (mm)</u> 12	<u>Max operating pressure (at 20°C) (bar)</u> 10	<u>Colour</u> Black
<u>Temperature</u> - 20°C to +70°C	<u>Construction</u> Polyurethane	<u>Applications</u> Compact air transport	<u>Highlight</u> Food compliant (FDA) - Only for PHCR white tubes -

Description				
Reference	ID/OD (mm)	Mini bend radius (mm)	Max operating pressure (at 20°C) (bar)	Colour
PHBK M2504100	2.5 x 4	12	10	Black

Reference	ID/OD (mm)	Mini bend radius (mm)	Max operating pressure (at 20°C (bar))	Colour
PHBE M2504100	2.5 x 4	12	10	Blue
PHCR M2504100	2.5 x 4	12	10	White
PHBK M0406100	4 x 6	20	9	Black
PHBE M0406100	4 x 6	20	9	Blue
PHCR M0406100	4 x 6	20	9	White
PHBK M5508100	5.5 x 8	25	8.5	Black
PHBE M5508100	5.5 x 8	25	8.5	Blue
PHCR M5508100	5.5 x 8	25	8.5	White
PHBK M0710100	7 x 10	35	8.5	Black
PHBE M0710100	7 x 10	35	8.5	Blue
PHCR M0710100	7 x 10	35	8.5	White
PHBK M0812100	8 x 12	40	9	Black
PHBE M0812100	8 x 12	40	9	Blue
PHCR M0812100	8 x 12	40	9	White

