

Polyurethane tube Ether base in 25 meter-box (unit of sales = 1 box)



ID/OD (mm) 2.5 x 4	Mini bend radius (mm) 12	Max operating pressure (at 20°C (bar)) 10	Colour Black
Temperature - 20°C to +70°C	Construction Polyurethane	Applications Compact air transport	Highlight Food compliant (FDA) - Only for PHCR white tubes -

Description				
Reference	ID/OD (mm)	Mini bend radius (mm)	Max operating pressure (at 20°C (bar))	Colour
PHBK M250425	2.5 x 4	12	10	Black

Reference	ID/OD (mm)	Mini bend radius (mm)	Max operating pressure (at 20°C (bar)	Colour
PHBE M250425	2.5 x 4	12	10	Blue
PHCR M250425	2.5 x 4	12	10	White
PHBK M040625	4 x 6	20	9	Black
PHBE M040625	4 x 6	20	9	Blue
PHCR M040625	4 x 6	20	9	White
PHBK M550825	5.5 x 8	25	8.5	Black
PHBE M550825	5.5 x 8	25	8.5	Blue
PHCR M550825	5.5 x 8	25	8.5	White
PHBK M071025	7 x 10	35	8.5	Black
PHBE M071025	7 x 10	35	8.5	Blue
PHCR M071025	7 x 10	35	8.5	White
PHBK M081225	8 x 12	40	9	Black
PHBE M081225	8 x 12	40	9	Blue
PHCR M081225	8 x 12	40	9	White
PHCR M951425	9.5 x 14	50	9	White

